



## **Chapter 4**

# **Weather and penthouse louvres**

## Chapter 4

### Weather and penthouse louvres

#### Penthouse louvres

New!



**New series combi penthouse louvre (June 2025)** 3  
New design  
Combi penthouse louvre  
Separate supply and return hood possible



**BDXN/BDYN** 4  
Steel/Aluminium  
Standard version



**BDWN** 8  
Aluminium  
Limited height

#### Weather louvres



**BMXN/BMXT** 12  
Steel  
With/Without flange



**BMYN/BMYT** 17  
Aluminium  
With/Without flange



**BMZN** 22  
Aluminium  
Customised



**BMUF/BMUD** 26  
Burglar-proof  
Wall/Door



**BMUF-K** 30  
Burglar-proof  
Blind fitting



**BKVN** 34  
Sound attenuating  
Steel



**BMDRSO** 38  
Round  
Aluminium



## Combined penthouse louvre (June 2025)

**New design  
Combi penthouse louvre  
Separate supply and return hood possible**

**Our new range of penthouse louvre are available from June 2025!**



This new line will initially be carried alongside our current product line of penthouse louvre. With the new 'design' line, we took a good look at the functionality and operation of the louvre.

The new line is expected to be available from the beginning of 2025. Keep an eye on our website for the technical documentation and prices or stay informed via our newsletter.

You can register online:  
[nijburg.nl/nieuwsbrief-aanmelding](http://nijburg.nl/nieuwsbrief-aanmelding)

### The most important features:

- Vertical return is done at speed of 5 m/s to 10 m/s to keep the polluted air as far as possible away from the supply.
- Due to the increased supply device, the physical distance between supply and return is increased, reducing short circuits to a minimum.
- The fresh air is sucked in on 4 sides of the combi penthouse louvre.
- Drainage of the roof and return collection takes place "by" the corner posts, which prevent rainwater from flowing over the return diffusers.
- Patented rain protection in the return duct.
- To be installed on in-situ roof base and optional versions.
- The Louvres are made entirely of aluminium and are also provided with a polyester powder coating.





## BDXN/BDYN

### Penthouse louver Standard version Weatherproof vane

#### Available types

##### B D - N - O

- B** outside air
- D** penthouse louver

#### - Material

- X** rolled sendzimir galvanised steel vane 60 mm
- Y** anodised aluminium vane 50 mm

- N** starter frame for upstand

#### - Mesh

- G** galvanised mesh (standard)
- S** stainless steel insect mesh

- O** not applicable

#### Available upstands

- BDONOD:** uninsulated, sendzimir galvanised steel
- BDONOR:** insulated, sendzimir galvanised steel
- BDONAD:** uninsulated, seawater-resistant aluminium
- BDONAR:** insulated, seawater-resistant aluminium

#### Available uninsulated grommets

- BDOKOD:** sendzimir galvanised steel, length 500 mm
- BDOKAD:** seawater-resistant aluminium, length 500 mm

#### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

#### Use

The BD-N penthouse louver is suitable for air supply or discharge. The penthouse louver is available to extremely large dimensions in order to combine the air supply or discharge for several ventilation systems. It is also possible to have the penthouse louver as a combined supply and discharge.

#### Characteristics

Standard fitted with hoisting rings.

#### Version

##### Penthouse louver BDXN

Material:	sendzimir galvanised steel
Mesh:	19 x 19 mm, galvanised
Louvres:	sendzimir galvanised steel
Frame + penthouse:	sendzimir galvanised steel
Post-treatment:	none

#### Optional

Insect mesh*:	stainless steel 2 x 2 mm
---------------	--------------------------

##### Penthouse louver BDYN


Material:	seawater-resistant aluminium
Mesh:	19 x 19 mm, galvanised
Louvres:	anodised aluminium
Frame + penthouse:	seawater-resistant aluminium
Post-treatment:	none

#### Optional

Insect mesh*:	stainless steel, 2 x 2 mm
---------------	---------------------------

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in [SA-Select](#).

## Dimensions



## Available dimensions and weights

W		L									
		600	800	1000	1200	1400	1600	1800	2000	2200	2400
600	H	500	600	600	700	700	700	700	700	700	800
	BDX kg	60	75	85	100	110	120	130	140	150	175
	BDY kg	25	35	40	50	55	60	65	70	75	90
800	H		700	700	800	800	900	900	900	900	900
	BDX kg		90	100	120	130	155	165	180	190	200
	BDY kg		45	50	60	65	80	85	90	95	105
1000	H			800	900	900	1000	1000	1000	1000	1100
	BDX kg			120	145	155	180	190	205	215	245
	BDY kg			60	75	80	90	100	105	110	130
1200	H				1000	1000	1100	1100	1200	1200	1200
	BDX kg				170	180	205	220	250	260	275
	BDY kg				85	90	105	115	130	140	145
1400	H					1100	1200	1200	1300	1300	1400
	BDX kg					205	235	250	280	295	325
	BDY kg					105	125	130	150	155	175
1600	H						1200	1300	1400	1400	1400
	BDX kg						250	280	310	325	345
	BDY kg						130	150	165	175	185
1800	H							1400	1400	1500	1600
	BDX kg							310	325	360	400
	BDY kg							165	175	195	215

## Note

- The listed dimensions are in mm.

## Selection details

BD-N

Table 1.1: Supply (with L x W = 1600 x 1600 mm)

		2	3	4	5	6	7	m/s
BDXN steel	$\Delta p_s$	6	12	22	39	54	71	Pa
	$L_{pA}$	22	32	40	48	52	56	dB(A)
BDYN aluminium	$\Delta p_s$	7	17	27	44	69	86	Pa
	$L_{pA}$	24	36	42	48	55	58	dB(A)

Table 1.2: Discharge (with L x W = 1600 x 1600 mm)

		2	3	4	5	6	7	m/s
BDXN steel	$\Delta p_s$	6	12	22	39	54	71	Pa
	$L_{pA}$	19	29	37	45	49	59	dB(A)
BDYN aluminium	$\Delta p_s$	6	14	23	37	58	72	Pa
	$L_{pA}$	21	33	39	45	52	55	dB(A)

Table 2: Required passage surface

air volume		m/s					
m <sup>3</sup> /s	m <sup>3</sup> /h	2	3	4	5	6	7
		m <sup>2</sup>					
0.60	2160	0.30	0.20	0.15	0.12	0.10	0.09
0.80	2880	0.40	0.27	0.20	0.16	0.13	0.11
1.00	3600	0.50	0.33	0.25	0.20	0.17	0.14
1.50	5400	0.75	0.50	0.38	0.30	0.25	0.21
2.00	7200	1.00	0.67	0.50	0.40	0.33	0.29
2.50	9000	1.25	0.83	0.63	0.50	0.42	0.36
3.00	10800	1.50	1.00	0.75	0.60	0.50	0.43
4.00	14400	2.00	1.33	1.00	0.80	0.67	0.57
5.00	18000	2.50	1.67	1.25	1.00	0.83	0.71
6.00	21600	3.00	2.00	1.50	1.20	1.00	0.86
8.00	28800	4.00	2.67	2.00	1.60	1.33	1.14
10.00	36000		3.33	2.50	2.00	1.67	1.43
15.00	54000			3.75	3.00	2.50	2.14
20.00	72000				4.00	3.33	2.86
25.00	90000					4.17	3.57
30.00	108000						4.29

Preferred range

Table 3: Passage and penthouse louvre height

W		L									
		600	800	1000	1200	1400	1600	1800	2000	2200	2400
600	H	500	600	600	700	700	700	700	700	700	800
	m <sup>2</sup>	0.36	0.48	0.60	0.72	0.84	0.96	1.08	1.20	1.32	1.44
800	H		700	700	800	800	900	900	900	900	900
	m <sup>2</sup>		0.64	0.80	0.96	1.12	1.28	1.44	1.60	1.76	2.00
1000	H			800	900	900	1000	1000	1000	1000	1100
	m <sup>2</sup>			1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40
1200	H				1000	1000	1100	1100	1200	1200	1200
	m <sup>2</sup>				1.44	1.68	1.92	2.16	2.40	2.64	2.88
1400	H					1100	1200	1200	1300	1300	1400
	m <sup>2</sup>					1.96	2.24	2.52	2.80	3.08	3.36
1600	H						1200	1300	1400	1400	1400
	m <sup>2</sup>						2.56	2.88	3.20	3.52	3.84
1800	H							1400	1400	1500	1600
	m <sup>2</sup>							3.24	3.60	3.96	4.32

## Note

- The listed dimensions are in mm.

Table 4: Sound correction for different dimensions

W	L									
	600	800	1000	1200	1400	1600	1800	2000	2200	2400
	dB	dB	dB	dB	dB	dB	dB	dB	dB	dB
600	-9	-7	-6	-6	-5	-4	-4	-3	-3	-2
800		-6	-5	-4	-4	-3	-2	-2	-2	-1
1000			-4	-3	-3	-2	-2	-1	-1	0
1200				-2	-2	-1	-1	0	0	1
1400					-1	-1	0	0	1	1
1600						0	1	1	1	2
1800							1	1	2	2

#### Note

- The maximum inflow speed is limited at 4 m/s in connection with the weatherproof limit.
- However, blow-through means the weatherproofness of penthouse louvres is not solely dependent on the inflow speed. It is recommended to fit a drainage option in the connecting duct.
- The given height is the optimum height. Lowering the penthouse louvre produces too much reduction in the passage. Increasing it produces an inefficient cost increase.
- $L_{pA} = L_{WA} - 10$  dB.
- The sound pressure  $L_{pA}$  is given for a penthouse louvre dimension of  $L \times W \times H = 1600 \times 1600 \times 1200$  mm. For correction with a different dimension, please refer to the sound correction table 4.
- The listed dimensions are in mm.

#### Selection example

- Determine the speed by using table 1.1 or 1.2 and the pressure loss and sound production that is deemed permissible.
- In combination with the air volume, table 2 is used to determine the required passage.
- Table 3 then provides the possible penthouse louvre dimensions.
- If the penthouse louvre has a dimension other than  $L \times W = 1600 \times 1600$  mm, correct the sound production in accordance with table 4.



## BDWN

### Penthouse louvre Limited height Weatherproof vane

#### Available types

##### **B D W N - O**

- B** outside air
- D** penthouse louvre
- W** seawater-resistant aluminium
- N** starter frame for upstands

##### - Mesh

- G** galvanised mesh (standard)
- S** stainless steel insect mesh

- O** not applicable

#### Available upstands

- BDONAD:** uninsulated, seawater-resistant aluminium
- BDONAR:** insulated, seawater-resistant aluminium

#### Available uninsulated grommets

- BDOKAD:** seawater-resistant aluminium, length = 500 mm

#### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

#### Use

The BDWN penthouse louvre is suitable for air supply or discharge, has an extremely limited height and an attractive design. The penthouse louvre is available to extremely large dimensions in order to combine the air supply or discharge for several ventilation systems. It is possible to have the penthouse louvre as a combined supply and discharge.

#### Characteristics

Standard fitted with hoisting rings.

#### Version

##### Penthouse louvre


- Material: seawater-resistant aluminium
- Mesh: 19 x 19 mm, galvanised

#### Optional

- Insect mesh\*: stainless steel, 2 x 2 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in SA-Select.

## Dimensions



## Available dimensions, sizes and weight

W		L									
		600	800	1000	1200	1400	1600	1800	2000	2200	2400
600	H	395	540	540	540	540	540	540	540	540	685
	O	275	320	320	320	320	320	320	320	320	370
	kg	12	19	22	25	28	30	33	36	38	51
800	H		540	540	540	685	685	685	685	685	685
	O		320	320	320	370	370	370	370	370	370
	kg		22	25	28	39	42	46	49	53	56
1000	H			540	685	685	685	685	830	830	830
	O			320	370	370	370	370	415	415	415
	kg			28	39	43	47	50	64	69	73
1200	H				685	685	830	830	830	830	830
	O				370	370	415	415	415	415	415
	kg				43	47	61	65	70	74	78
1400	H					830	830	830	830	830	975
	O					415	415	415	415	415	465
	kg					61	65	70	75	80	97
1600	H						830	830	975	975	975
	O						415	415	465	465	465
	kg						70	75	92	98	103
1800	H							975	975	975	975
	O							465	465	465	465
	kg							93	98	104	110

### Note

- The listed dimensions are in mm.

## Selection details

### BDWNG

Table 1.1: Supply (with L x W = 1200 x 1200 mm)

	V	3	4	5	6	7	m/s
BDWNGO	$\Delta p_s$	19	<b>33</b>	52	75	101	Pa
	$L_{pA}$	32	<b>41</b>	48	53	58	dB(A)

Table 1.2: Discharge (with L x W = 1200 x 1200 mm)

	V	3	4	5	6	7	m/s
BDWNGO	$\Delta p_s$	9	15	<b>24</b>	35	47	Pa
	$L_{pA}$	33	42	<b>49</b>	54	59	dB(A)

Table 2: Required passage surface

air volume		m/s					
m <sup>3</sup> /s	m <sup>3</sup> /h	2	3	4	5	6	7
		m <sup>2</sup>					
0.60	2160	0.30	0.20	<b>0.15</b>	<b>0.12</b>	0.10	0.09
0.80	2880	0.40	0.27	<b>0.20</b>	<b>0.16</b>	0.13	0.11
1.00	3600	0.50	0.33	<b>0.25</b>	<b>0.20</b>	0.17	0.14
1.50	5400	0.75	0.50	<b>0.38</b>	<b>0.30</b>	0.25	0.21
2.00	7200	1.00	0.67	<b>0.50</b>	<b>0.40</b>	0.33	0.29
2.50	9000	1.25	0.83	<b>0.63</b>	<b>0.50</b>	0.42	0.36
3.00	10800	1.50	1.00	<b>0.75</b>	<b>0.60</b>	0.50	0.43
4.00	14400	2.00	1.33	<b>1.00</b>	<b>0.80</b>	0.67	0.57
5.00	18000	2.50	1.67	<b>1.25</b>	<b>1.00</b>	0.83	0.71
6.00	21600	3.00	2.00	<b>1.50</b>	<b>1.20</b>	1.00	0.86
8.00	28800	4.00	2.67	<b>2.00</b>	<b>1.60</b>	1.33	1.14
10.00	36000		3.33	<b>2.50</b>	<b>2.00</b>	1.67	1.43
15.00	54000			<b>3.75</b>	<b>3.00</b>	2.50	2.14
20.00	72000				<b>4.00</b>	3.33	2.86
25.00	90000					4.17	3.57
30.00	108000						4.29

Preferred range

Table 3: Passage and penthouse louvre height

W		L									
		600	800	1000	1200	1400	1600	1800	2000	2200	2400
600	H	395	540	540	540	540	540	540	540	685	685
	m <sup>2</sup>	0.36	0.48	0.60	0.72	0.84	0.96	1.08	1.20	1.32	1.44
800	H		540	540	540	685	685	685	685	685	685
	m <sup>2</sup>		0.64	0.80	0.96	1.12	1.28	1.44	1.60	1.76	2.00
1000	H			540	685	685	685	685	830	830	830
	m <sup>2</sup>			1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40
1200	H				685	685	830	830	830	830	830
	m <sup>2</sup>				1.44	1.68	1.92	2.16	2.40	2.64	2.88
1400	H					830	830	830	830	975	975
	m <sup>2</sup>					1.96	2.24	2.52	2.80	3.08	3.36
1600	H						830	830	975	975	975
	m <sup>2</sup>						2.56	2.88	3.20	3.52	3.84
1800	H							975	975	975	1120
	m <sup>2</sup>							3.24	3.60	3.96	4.32

### Note

- The listed dimensions are in mm.

Table 4: Sound correction for different dimensions

W	L									
	600	800	1000	1200	1400	1600	1800	2000	2200	2400
	dB	dB	dB	dB	dB	dB	dB	dB	dB	dB
600	-6	-5	-4	-3	-2	-2	-1	-1	0	0
800	-5	-4	-3	-2	-1	-1	0	0	1	1
1000	-4	-3	-2	-1	0	0	1	1	2	2
1200	-3	-2	-1	0	1	1	2	2	3	3
1400	-2	-1	0	1	1	2	2	3	3	4
1600	-2	-1	0	1	2	2	3	3	4	4
1800	-1	0	1	2	2	3	4	4	4	5


**Note**

- The maximum inflow speed is limited at 4 m/s in connection with the weatherproof limit.
- However, blow-through means the weatherproofness of penthouse louvres is not solely dependent on the inflow speed. It is recommended to fit a drainage option in the connecting duct.
- The given height is the optimum height. Lowering the penthouse louvre produces too much reduction in the passage. Increasing it produces an inefficient cost increase.
- $LpA = LwA - 10 \text{ dB}$ .
- The sound pressure  $LpA$  is given for a penthouse louvre dimension of  $L \times W \times H = 1200 \times 1200 \times 685 \text{ mm}$ . For correction with a different dimension, please refer to the sound correction table 4.
- The listed dimensions are in mm.

**Selection example**

- Determine the speed by using table 1 and the pressure loss and sound production that is deemed permissible.
- In combination with the air volume, table 2 is used to determine the required passage.
- Table 3 then provides the possible penthouse louvre dimensions.
- If the penthouse louvre has a dimension other than  $L \times W = 1200 \times 1200 \text{ mm}$ , correct the sound production in accordance with table 4.

**Fitting**



2025\_02\_V1



## BMXN/BMXT

**Weather louvre**  
**Steel**  
**Weatherproof vane**

### Available types

**B M X - - -**

- B** weather louvre
  - M** wall louvre
  - X** rolled sendzimir galvanised steel vane 60 mm
- **Frame**
    - N** sendzimir galvanised steel frame 45 mm, fixed
    - T** sendzimir galvanised steel frame, without flange
  - **Mesh**
    - G** galvanised mesh (standard)
    - S** stainless steel insect mesh
  - **Accessories**
    - O** none
    - I** mounting frame, sendzimir galvanised steel (BMXN only)

### SA-Select

Check [SA-Select](#) to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online..

### Use

The BMX- weather louvre is suitable for air supply or discharge. The BMXN louvre can be fitted in the external wall with a mounting frame; see note. The BMXT louvre does not have a flange.

### Characteristics

Free flow: 20 - 55 % (depending on the height)  
 Weight: approx. 30 kg/m<sup>2</sup>

### Version

#### Weather louvre


Frame: sendzimir galvanised steel  
 Vanes: sendzimir galvanised steel  
 Post-treatment: none  
 Mesh: 19 x 19 mm, galvanised

### Optional


Insect mesh\*: stainless steel, 2 x 2 mm  
 Mounting frame: sendzimir galvanised steel  
 Mounting holes: Ø 4.5 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in [SA-Select](#).

## Dimensions



## Dimensions



### Standard dimensions

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
325	■	■	■	■	■	■	■	■	■
525	■	■	■	■	■	■	■	■	■
825	■	■	■	■	■	■	■	■	■
1025	■	■	■	■	■	■	■	■	■
1225	■	■	■	■	■	■	■	■	■
1425	■	■	■	■	■	■	■	■	■
1625	■	■	■	■	■	■	■	■	■
1825	■	■	■	■	■	■	■	■	■
2025	■	■	■	■	■	■	■	■	■

### Available dimensions

- Interim sizes available in increments of 5 mm.
- Larger dimensions (W max. = 4000, H max. 2025) are available on request (2-part).

### Note

- It is recommended to fit a drainage option in the duct behind the louvres.
- BMXT is suitable for flush mounting. Remember the drainage facility when the louvre is flush mounted in an external wall.
- The listed dimensions are in mm.
- Recess size: W x H (with a mounting frame, the recess is W + 10 x H + 10).

## Selection details

### BMX-G

air volume		required free flow in m <sup>2</sup>											
		0.05		0.06		0.08		0.1		0.125		0.15	
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)
0.080	<b>288</b>	5	5										
0.100	<b>360</b>	8	10	6	6								
0.150	<b>540</b>	19	21	13	17	7	11	5	6				
0.200	<b>720</b>	33	28	23	25	13	18	8	13	5	9	4	5
0.250	<b>900</b>	51	34	36	30	20	24	13	19	8	14	6	10
0.300	<b>1080</b>	74	39	51	35	29	29	19	24	12	19	8	15
0.400	<b>1440</b>	132	47	91	43	51	36	33	32	21	27	15	23
0.500	<b>1800</b>					80	42	51	37	33	32	23	29
0.600	<b>2160</b>					116	47	74	42	47	37	33	33
0.800	<b>2800</b>									84	45	59	41
1.000	<b>3600</b>									132	51	91	47

air volume		required free flow in m <sup>2</sup>																							
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2			
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)	$\Delta p_t$ Pa	$L_{pk}$ dB(A)		
0.250	<b>900</b>	3	4																						
0.300	<b>1080</b>	5	9	3	4																				
0.400	<b>1440</b>	8	16	5	12	4	8																		
0.500	<b>1800</b>	13	22	8	17	6	13	3	7																
0.600	<b>2160</b>	19	27	12	22	8	18	5	12	3	7														
0.800	<b>2800</b>	33	35	21	30	15	26	8	19	5	15	4	11												
1.000	<b>3600</b>	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5								
1.500	<b>5400</b>	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7				
2.000	<b>7200</b>			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8		
2.500	<b>9000</b>					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14		
3.000	<b>10800</b>							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19		
4.000	<b>14400</b>									132	57	91	53	51	46	33	42	21	37	15	33	8	26		
5.000	<b>18000</b>											143	58	80	52	51	47	33	42	23	39	13	32		
6.000	<b>21600</b>													116	57	74	52	47	47	33	43	19	37		
8.000	<b>28800</b>														132	60	84	55	59	51	33	45			
10.000	<b>36000</b>															132	61	91	57	51	51	50			

Preferred range (approx. 4 m/s over net surface).

#### General

- $L_{pA} = L_{wA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

#### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1.2$ .  
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
	m <sup>2</sup>								
<b>325</b>	0.0388	0.0580	0.0772	0.0964	0.1156	0.1348	0.1540	0.1732	0.1924
<b>525</b>	0.0905	0.1353	0.1801	0.2249	0.2697	0.3145	0.3593	0.4041	0.4489
<b>825</b>	0.1551	0.2319	0.3087	0.3855	0.4623	0.5391	0.6159	0.6927	0.7695
<b>1025</b>	0.1939	0.2899	0.3859	0.4819	0.5779	0.6739	0.7699	0.8659	0.9619
<b>1225</b>	0.2327	0.3479	0.4631	0.5783	0.6935	0.8087	0.9239	1.0391	1.1543
<b>1425</b>	0.2844	0.4252	0.5660	0.7068	0.8476	0.9884	1.1292	1.2700	1.4108
<b>1625</b>	0.3232	0.4832	0.6432	0.8032	0.9632	1.1232	1.2832	1.4432	1.6032
<b>1825</b>	0.3620	0.5412	0.7204	0.8996	1.0788	1.2580	1.4372	1.6164	1.7956
<b>2025</b>	0.4137	0.6185	0.8233	1.0281	1.2329	1.4377	1.6425	1.8473	2.0521



## BMYN/BMYT

**Weather louvre**  
**Aluminium**  
**Weatherproof vane**

### Available types

**BMY---**

- B** weather louvre
- M** wall louvre
- Y** anodised aluminium vane 50 mm

#### - Frame

- N** anodised aluminium frame 40 mm, fixed
- T** seawater-resistant aluminium frame, without flange

#### - Mesh

- G** galvanised mesh (standard)
- S** stainless steel insect mesh

#### - Accessories

- O** none
- I** mounting frame, sendzimir galvanised steel (BMYN only)

### SA-Select

Check [SA-Select](#) to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

### Use

The BMY- weather louvre is suitable for air supply or discharge. The BMYN louvre can be fitted in the external wall with a mounting frame; see note. The BMYT louvre does not have a flange.

### Characteristics

Free flow: 20 - 55 % (depending on the height)  
 Weight: approx. 15 kg/m<sup>2</sup>

### Version

#### Weather louvre

Frame: BMYN: anodised aluminium  
 BMYT: seawater-resistant

Aluminium

Vanes: anodised aluminium

Post-treatment: BMYN: none  
 BMYT: RAL colour of your choice

Mesh: 19 x 19 mm, galvanised

### Optional


Insect mesh\*: stainless steel, 2 x 2 mm

Mounting frame: sendzimir galvanised steel


Mounting holes: Ø 4.5 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in [SA-Select](#).

## Dimensions



## Dimensions



### Standard dimensions

#### Available dimensions

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
325	■	■	■	■	■	■	■	■	■
525	■	■	■	■	■	■	■	■	■
825	■	■	■	■	■	■	■	■	■
1025	■	■	■	■	■	■	■	■	■
1225	■	■	■	■	■	■	■	■	■
1425	■	■	■	■	■	■	■	■	■
1625	■	■	■	■	■	■	■	■	■
1825	■	■	■	■	■	■	■	■	■
2025	■	■	■	■	■	■	■	■	■

- Width min. 300, max. 2025.
- Height min. 300, max. 2025.
- Interim widths and heights available in increments of 5 mm.
- Larger dimensions up to WxH 4000x2025 mm are available on request (delivered in two parts).
- Louvres in parts must always be provided with a finish in RAL color of choice.

- For sizes larger than WxH 4000x2025 mm, please consult the [documentation](#) of the louvre type BMZN.

#### Note

- When the BMYN-I with mounting frame (cross-section 60 x 30 x 2 mm) is used, the recess must be made 10 mm larger than the nominal W x H louvre size.
- It is recommended to fit a drainage option in the duct behind the louvres.
- BMYT is suitable for flush mounting. Remember the drainage facility when the louvre is flush mounted in an external wall.
- The listed dimensions are in mm.
- Recess size: W x H.

## Selection details

### BMY-G

air volume		required free flow in m <sup>2</sup>											
		0.05		0.06		0.08		0.1		0.125		0.15	
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)
0.080	<b>288</b>	5	5										
0.100	<b>360</b>	8	10	6	6								
0.150	<b>540</b>	19	21	13	17	7	11	5	6				
0.200	<b>720</b>	33	28	23	25	13	18	8	13	5	9	4	5
0.250	<b>900</b>	51	34	36	30	20	24	13	19	8	14	6	10
0.300	<b>1080</b>	74	39	51	35	29	29	19	24	12	19	8	15
0.400	<b>1440</b>	132	47	91	43	51	36	33	32	21	27	15	23
0.500	<b>1800</b>					80	42	51	37	33	32	23	29
0.600	<b>2160</b>					116	47	74	42	47	37	33	33
0.800	<b>2800</b>									84	45	59	41
1.000	<b>3600</b>									132	51	91	47

air volume		required free flow in m <sup>2</sup>																						
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2		
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	
0.250	<b>900</b>	3	4																					
0.300	<b>1080</b>	5	9	3	4																			
0.400	<b>1440</b>	8	16	5	12	4	8																	
0.500	<b>1800</b>	13	22	8	17	6	13	3	7															
0.600	<b>2160</b>	19	27	12	22	8	18	5	12	3	7													
0.800	<b>2800</b>	33	35	21	30	15	26	8	19	5	15	4	11											
1.000	<b>3600</b>	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5							
1.500	<b>5400</b>	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7			
2.000	<b>7200</b>			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8	
2.500	<b>9000</b>					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14	
3.000	<b>10800</b>							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19	
4.000	<b>14400</b>									132	57	91	53	51	46	33	42	21	37	15	33	8	26	
5.000	<b>18000</b>											143	58	80	52	51	47	33	42	23	39	13	32	
6.000	<b>21600</b>													116	57	74	52	47	47	33	43	19	37	
8.000	<b>28800</b>														132	60	84	55	59	51	33	45		
10.000	<b>36000</b>																	132	61	91	57	51	50	

Preferred range (approx. 4 m/s over net surface).

#### General

- $L_{pA} = L_{WA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

#### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1.2$   
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
	m <sup>2</sup>								
<b>325</b>	0.0426	0.0634	0.0842	0.1050	0.1258	0.1466	0.1674	0.1882	0.2090
<b>525</b>	0.0853	0.1269	0.1685	0.2101	0.2517	0.2933	0.3349	0.3765	0.4181
<b>825</b>	0.1492	0.2220	0.2948	0.3676	0.4404	0.5132	0.5860	0.6588	0.7316
<b>1025</b>	0.1919	0.2855	0.3791	0.4727	0.5663	0.6599	0.7535	0.8471	0.9407
<b>1225</b>	0.2345	0.3489	0.4633	0.5777	0.6921	0.8065	0.9209	1.0353	1.1497
<b>1425</b>	0.2772	0.4124	0.5476	0.6828	0.8180	0.9532	1.0884	1.2236	1.3588
<b>1625</b>	0.3198	0.4758	0.6318	0.7878	0.9438	1.0998	1.2558	1.4118	1.5678
<b>1825</b>	0.3624	0.5392	0.7160	0.8928	1.0696	1.2464	1.4232	1.6000	1.7768
<b>2025</b>	0.4051	0.6027	0.8003	0.9979	1.1955	1.3931	1.5907	1.7883	1.9859



## BMZN

### Weather louvre (customised) Aluminium Weatherproof vane

#### Available types

**B M Z N - -**

- B** weather louvre
- M** wall louvre
- Z** anodised aluminium vane 66 mm
- N** anodised aluminium frame 50 mm, fixed

#### - Mesh

- G** galvanised mesh (standard)
- S** stainless steel insect mesh

#### - Accessories

- I** burglar protection
- W** drainage duct (only in combination with stainless steel insect mesh)
- X** burglar protection + drainage duct (only in combination with stainless steel insect mesh)
- O** none

#### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

#### Use

The BMZN louvre is suitable for air supply or discharge. The louvre is available as a customised alternative to the BMYN louvre. The louvre can be combined to extremely large sizes by putting together two or more segments. The maximum segment size is 6 metres wide and 2.4 metres high in connection with transport. The louvre is also available in different shapes, such as: triangle, round, trapezium. Diffusers in different shapes are welded and therefore should always be spray painted in color. Standard composite louvres are also available to  $W \times H = 4000 \times 2025$  mm in the more economical BMYN version.

#### Characteristics

Free flow:	53 %
Fixed blind vanes*:	66 mm
Weight:	approx. 16.5 kg/m <sup>2</sup>

\*At the top of the louvre, any remaining space is covered with an insert.

#### Version

##### Weather louvre


Frame:	anodised aluminium
Vaness:	anodised aluminium
Post-treatment:	none
Mesh:	10 x 10 mm, galvanised

##### Optional


Insect mesh*:	stainless steel, 1.4 x 1.4 mm
---------------	-------------------------------

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in SA-Select.

## Dimensions



## Formats



The maximum width and height may cover the façade.

## Note

- The listed dimensions are in mm.
- $W \times H$  is the recess size.
- Blind anchoring with screws requires the removal of one vane, following which a hole can be drilled in the frame; see right view above. After fitting the louvre, the removed vane can be put back and will cover the screw.
- When burglar protection is used, the louvre needs to be fitted from the inside.
- It is recommended to fit a drainage option in the duct behind the louvres. At the front, the standard drainage duct discharges to the outside below the lowest vane.

## Selection details

### BMZNG

air volume		required free flow in m <sup>2</sup>											
		0.05		0.06		0.08		0.1		0.125		0.15	
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)
0.080	<b>288</b>	5	5										
0.100	<b>360</b>	8	10	6	6								
0.150	<b>540</b>	19	21	13	17	7	11	5	6				
0.200	<b>720</b>	33	28	23	25	13	18	8	13	5	9	4	5
0.250	<b>900</b>	51	34	36	30	20	24	13	19	8	14	6	10
0.300	<b>1080</b>	74	39	51	35	29	29	19	24	12	19	8	15
0.400	<b>1440</b>	132	47	91	43	51	36	33	32	21	27	15	23
0.500	<b>1800</b>					80	42	51	37	33	32	23	29
0.600	<b>2160</b>					116	47	74	42	47	37	33	33
0.800	<b>2800</b>									84	45	59	41
1.000	<b>3600</b>									132	51	91	47

air volume		required free flow in m <sup>2</sup>																						
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2		
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	
0.250	<b>900</b>	3	4																					
0.300	<b>1080</b>	5	9	3	4																			
0.400	<b>1440</b>	8	16	5	12	4	8																	
0.500	<b>1800</b>	13	22	8	17	6	13	3	7															
0.600	<b>2160</b>	19	27	12	22	8	18	5	12	3	7													
0.800	<b>2800</b>	33	35	21	30	15	26	8	19	5	15	4	11											
1.000	<b>3600</b>	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5							
1.500	<b>5400</b>	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7			
2.000	<b>7200</b>			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8	
2.500	<b>9000</b>					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14	
3.000	<b>10800</b>							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19	
4.000	<b>14400</b>									132	57	91	53	51	46	33	42	21	37	15	33	8	26	
5.000	<b>18000</b>											143	58	80	52	51	47	33	42	23	39	13	32	
6.000	<b>21600</b>													116	57	74	52	47	47	33	43	19	37	
8.000	<b>28800</b>														132	60	84	55	59	51	33	35	45	
10.000	<b>36000</b>																	132	61	91	57	51	50	

Preferred range (approx. 4 m/s over net surface).

#### General

- $L_{pA} = L_{WA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

#### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1,2$   
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	W													
	425	625	825	1025	1225	1425	1625	1825	2025	3025	4025	5025	6000	
	m <sup>2</sup>													
<b>325</b>	0.0522	0.0775	0.1026	0.1279	0.1531	0.1783	0.2035	0.2287	0.2538	0.3791	0.5044	0.6298	0.7551	
<b>525</b>	0.1026	0.1520	0.2015	0.2509	0.3003	0.3498	0.3992	0.4487	0.4981	0.7440	0.9900	1.2360	1.4820	
<b>825</b>	0.1792	0.2656	0.3520	0.4384	0.5248	0.6112	0.6976	0.7840	0.8704	1.3002	1.7300	2.1599	2.5597	
<b>1025</b>	0.2232	0.3308	0.4384	0.5460	0.6536	0.7612	0.8688	0.9764	1.0840	1.6193	2.1546	2.6898	3.2118	
<b>1225</b>	0.2672	0.3960	0.5248	0.6536	0.7824	0.9112	1.0400	1.1688	1.2976	1.9383	2.5791	3.2199	3.8447	
<b>1425</b>	0.3854	0.4612	0.6112	0.7612	0.9112	1.0612	1.2112	1.3612	1.5112	2.2574	3.0036	3.7499	4.4774	
<b>1625</b>	0.3552	0.5264	0.6976	0.8688	1.0400	1.2112	1.3824	1.5536	1.7247	2.5764	3.4281	4.2798	5.1102	
<b>1825</b>	0.3992	0.5916	0.7840	0.9764	1.1688	1.3612	1.5536	1.7459	1.9383	2.8954	3.8526	4.8098	5.7431	
<b>2025</b>	0.4432	0.6568	0.8704	1.0840	1.2976	1.5112	1.7247	1.9383	2.1519	3.2145	4.2771	5.3397	6.3758	
<b>2225</b>	0.4919	0.7233	0.9548	1.1863	1.4178	1.6493	1.8807	2.1122	2.3437	3.5011	4.6585	5.8200	6.9444	
<b>2400</b>	0.5411	0.7957	1.0503	1.3050	1.5596	1.8142	2.0609	2.3235	2.5781	3.8513	5.1245	6.3977	7.6390	



## BMUF/BMUD

**Weather louvres**  
**Burglar-proof version**  
**Hot-dip galvanised**

### Available types

#### BMU--Q

- B** weather louvre
  - M** wall louvre
  - U** set hot-dip galvanised steel vane 70 mm, with reinforcement strips
- **Frame**
    - F** wall mounting with U-profile frame and strips, for a wall thickness up to 270 mm
    - D** door mounting with holes in the flange
  - **Mesh**
    - Q** mess, cold rolled (standard)
    - S** stainless steel insect mesh
  - Q** burglar-proof blind mounting

### SA-Select

Check [SA-Select](#) to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

### Use

The BMU--Q weather louvre is suitable for air supply or discharge. The louvre is fitted in the wall with fixing strips and a corresponding counter frame. The BMUD-Q louvre has holes in the flange, so that carriage bolts can be used to mount it directly in a door.

### Characteristics

Free flow: 20 - 55 % (depending on the height)  
 Weight: approx. 35 kg/m<sup>2</sup>

### Version

#### Weather louvre


Frame: hot-dip galvanised steel  
 Vanes: hot-dip galvanised steel  
 Mesh: 10 x 10 mm, hot-dip galvanised steel

### Optional

Insect mesh\*: stainless steel, 2 x 2 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in [SA-Select](#).

## Dimensions



## Standard dimensions

H	B								
	425	625	825	1025	1225	1425	1625	1825	2025
325	■	■	■	■	■	■	■	■	■
525	■	■	■	■	■	■	■	■	■
825	■	■	■	■	■	■	■	■	■
1025	■	■	■	■	■	■	■	■	■
1225	■	■	■	■	■	■	■	■	■
1425	■	■	■	■	■	■	■	■	■
1625	■	■	■	■	■	■	■	■	■
1825	■	■	■	■	■	■	■	■	■
2025	■	■	■	■	■	■	■	■	■

## Note

- The louvre is fully hot-dip galvanized with a minimum zinc layer thickness according to NEN EN ISO 1461 (not centrifuged, average thickness 55  $\mu\text{m}$ , 395  $\text{g}/\text{m}^2$ ).
- It is recommended to fit a drainage option in the duct behind the louvres.
- Interim widths and heights available in increments of 5 mm.
- The listed dimensions are in mm.
- Recess size: W x H.

## Selection details

### BMU-Q

air volume		required free flow in m <sup>2</sup>											
		0.05		0.06		0.08		0.1		0.125		0.15	
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)
0.080	<b>288</b>	5	5										
0.100	<b>360</b>	8	10	6	6								
0.150	<b>540</b>	19	21	13	17	7	11	5	6				
0.200	<b>720</b>	33	28	23	25	13	18	8	13	5	9	4	5
0.250	<b>900</b>	51	34	36	30	20	24	13	19	8	14	6	10
0.300	<b>1080</b>	74	39	51	35	29	29	19	24	12	19	8	15
0.400	<b>1440</b>	132	47	91	43	51	36	33	32	21	27	15	23
0.500	<b>1800</b>					80	42	51	37	33	32	23	29
0.600	<b>2160</b>					116	47	74	42	47	37	33	33
0.800	<b>2800</b>									84	45	59	41
1.000	<b>3600</b>									132	51	91	47

air volume		required free flow in m <sup>2</sup>																						
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2		
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	
0.250	<b>900</b>	3	4																					
0.300	<b>1080</b>	5	9	3	4																			
0.400	<b>1440</b>	8	16	5	12	4	8																	
0.500	<b>1800</b>	13	22	8	17	6	13	3	7															
0.600	<b>2160</b>	19	27	12	22	8	18	5	12	3	7													
0.800	<b>2800</b>	33	35	21	30	15	26	8	19	5	15	4	11											
1.000	<b>3600</b>	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5							
1.500	<b>5400</b>	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7			
2.000	<b>7200</b>			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8	
2.500	<b>9000</b>					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14	
3.000	<b>10800</b>							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19	
4.000	<b>14400</b>									132	57	91	53	51	46	33	42	21	37	15	33	8	26	
5.000	<b>18000</b>											143	58	80	52	51	47	33	42	23	39	13	32	
6.000	<b>21600</b>													116	57	74	52	47	47	33	43	19	37	
8.000	<b>28800</b>														132	60	84	55	59	51	33	45		
10.000	<b>36000</b>																	132	61	91	57	51	50	

Preferred range (approx. 4 m/s over net surface).

#### General


- $L_{pA} = L_{WA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

#### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1.2$   
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
	m <sup>2</sup>								
<b>325</b>	0.0488	0.0738	0.0988	0.1238	0.1488	0.1738	0.1988	0.2238	0.2488
<b>525</b>	0.0878	0.1328	0.1778	0.2228	0.2678	0.3128	0.3578	0.4028	0.4478
<b>825</b>	0.1463	0.2213	0.2963	0.3713	0.4463	0.5213	0.5963	0.6713	0.7463
<b>1025</b>	0.1853	0.2803	0.3753	0.4703	0.5653	0.6603	0.7553	0.8503	0.9453
<b>1225</b>	0.2243	0.3393	0.4543	0.5693	0.6843	0.7993	0.9143	1.0293	1.1443
<b>1425</b>	0.2633	0.3983	0.5333	0.6683	0.8033	0.9383	1.0733	1.2083	1.3433
<b>1625</b>	0.3023	0.4573	0.6123	0.7673	0.9223	1.0773	1.2323	1.3873	1.5423
<b>1825</b>	0.3413	0.5163	0.6913	0.8663	1.0413	1.2163	1.3913	1.5663	1.7413
<b>2025</b>	0.3803	0.5753	0.7703	0.9653	1.1603	1.3553	1.5503	1.7453	1.9403



## BMUF-K

**Weather louvre**  
**Burglar-proof version**  
**Blind fitting from the outside**

### Available types

#### BMUF-K

- B** weather louvre
- M** wall louvre
- U** set hot-dip galvanised steel vane 70 mm, with reinforcement strips
- F** frame 54 mm
  
- **Mesh**
  - Q** mesh, cold rolled (standard)
  - S** stainless steel insect mesh
  
- K** burglar-proof blind mounting with a mounting frame with spring clips for click mounting the louvre

### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

### Use

The BMUFQK louvre is suitable for air supply or discharge. The louvre is mounted in the wall with a corresponding mounting frame with springs for click mounting the louvre. The louvre can be fitted from the outside of the building without disassembling the connection ducts. The louvre has been developed to replace existing, non burglar-proof, weather louvres.

### Characteristics

Free flow: 20 - 55 % (depending on the height)  
 Weight: approx. 35 kg/m<sup>2</sup>

### Version

#### Weather louvre


Frame: hot-dip galvanised steel  
 Vanes: hot-dip galvanised steel  
 Mesh: 10 x 10 mm, hot-dip galvanised steel  
 Mounting frame: hot-dip galvanised steel  
 Spring clips: stainless steel, centre-to-centre 300 mm

### Optional

Insect mesh\*: stainless steel, 2 x 2 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in SA-Select.

## Dimensions



### Standard dimensions

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
325	■	■	■	■	■	■	■	■	■
525	■	■	■	■	■	■	■	■	■
825	■	■	■	■	■	■	■	■	■
1025	■	■	■	■	■	■	■	■	■
1225	■	■	■	■	■	■	■	■	■
1425	■	■	■	■	■	■	■	■	■
1625	■	■	■	■	■	■	■	■	■
1825	■	■	■	■	■	■	■	■	■
2025	■	■	■	■	■	■	■	■	■

### Available dimensions

- Interim widths and heights available in increments of 5 mm.

### Opmerking

- The louvre is fully hot-dip galvanized with a minimum zinc layer thickness according to NEN EN ISO 1461 (not centrifuged, average thickness 55  $\mu\text{m}$ , 395  $\text{g}/\text{m}^2$ ).
- It is recommended to fit a drainage option in the duct behind the louvres.
- The listed dimensions are in mm.
- Recess size:  $W + 30 \times H + 30$ .

## Selection details

### BMUFQ

air volume		required free flow in m <sup>2</sup>											
		0.05		0.06		0.08		0.1		0.125		0.15	
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)
0.080	<b>288</b>	5	5										
0.100	<b>360</b>	8	10	6	6								
0.150	<b>540</b>	19	21	13	17	7	11	5	6				
0.200	<b>720</b>	33	28	23	25	13	18	8	13	5	9	4	5
0.250	<b>900</b>	51	34	36	30	20	24	13	19	8	14	6	10
0.300	<b>1080</b>	74	39	51	35	29	29	19	24	12	19	8	15
0.400	<b>1440</b>	132	47	91	43	51	36	33	32	21	27	15	23
0.500	<b>1800</b>					80	42	51	37	33	32	23	29
0.600	<b>2160</b>					116	47	74	42	47	37	33	33
0.800	<b>2800</b>									84	45	59	41
1.000	<b>3600</b>									132	51	91	47

air volume		required free flow in m <sup>2</sup>																						
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2		
m <sup>3</sup> /s	m <sup>3</sup> /h	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	$\Delta p_t$ Pa	$L_{pA}$ dB(A)	
0.250	<b>900</b>	3	4																					
0.300	<b>1080</b>	5	9	3	4																			
0.400	<b>1440</b>	8	16	5	12	4	8																	
0.500	<b>1800</b>	13	22	8	17	6	13	3	7															
0.600	<b>2160</b>	19	27	12	22	8	18	5	12	3	7													
0.800	<b>2800</b>	33	35	21	30	15	26	8	19	5	15	4	11											
1.000	<b>3600</b>	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5							
1.500	<b>5400</b>	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7			
2.000	<b>7200</b>			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8	
2.500	<b>9000</b>					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14	
3.000	<b>10800</b>							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19	
4.000	<b>14400</b>									132	57	91	53	51	46	33	42	21	37	15	33	8	26	
5.000	<b>18000</b>											143	58	80	52	51	47	33	42	23	39	13	32	
6.000	<b>21600</b>													116	57	74	52	47	47	33	43	19	37	
8.000	<b>28800</b>														132	60	84	55	59	51	33	45		
10.000	<b>36000</b>																132	61	91	57	51	50		

Preferred range (approx. 4 m/s over net surface).

#### General

- $L_{pA} = L_{WA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

#### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1,2$   
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
	m <sup>2</sup>								
<b>325</b>	0.0488	0.0738	0.0988	0.1238	0.1488	0.1738	0.1988	0.2238	0.2488
<b>525</b>	0.0878	0.1328	0.1778	0.2228	0.2678	0.3128	0.3578	0.4028	0.4478
<b>825</b>	0.1463	0.2213	0.2963	0.3713	0.4463	0.5213	0.5963	0.6713	0.7463
<b>1025</b>	0.1853	0.2803	0.3753	0.4703	0.5653	0.6603	0.7553	0.8503	0.9453
<b>1225</b>	0.2243	0.3393	0.4543	0.5693	0.6843	0.7993	0.9143	1.0293	1.1443
<b>1425</b>	0.2633	0.3983	0.5333	0.6683	0.8033	0.9383	1.0733	1.2083	1.3433
<b>1625</b>	0.3023	0.4573	0.6123	0.7673	0.9223	1.0773	1.2323	1.3873	1.5423
<b>1825</b>	0.3413	0.5163	0.6913	0.8663	1.0413	1.2163	1.3913	1.5663	1.7413
<b>2025</b>	0.3803	0.5753	0.7703	0.9653	1.1603	1.3553	1.5503	1.7453	1.9403



## BKVN

### Weather louvre Sound attenuating Weatherproof vane

#### Available types

#### B K V N - O

- B** weather louvre
- K** sound attenuating
- V** flat face, galvanised steel sheet
- N** not applicable

#### - Mesh

- G** galvanised mesh (standard)
- S** stainless steel insect mesh

- O** not applicable

#### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

#### Use

The sound attenuating weather louvre BKVN is suitable for supplying and discharging air, when special requirements are imposed on the sound levels in the surrounding area. With the corresponding mounting frame, the louvre can be fitted in any type of wall. The sound attenuating weather louvre is suitable as a ventilation louvre for boiler houses, compressor rooms, et cetera.

#### Characteristics

Free flow: See further on in this document  
Weight: See further on in this document

#### Version

##### Weather louvre


Frame: sendzimir galvanised steel  
Vaness: sendzimir galvanised steel  
Attenuating material: mineral wool with glass-fibre covering  
Mesh: 19 x 19 mm, galvanised

#### Optional

Insect mesh\*: stainless steel, 2 x 2 mm

\*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in SA-Select.

## Dimensions



### Available dimensions and weights

H	W								
	320	520	720	920	1120	1320	1520	1720	1920
	kg	kg	kg	kg	kg	kg	kg	kg	kg
320	10	15	20	25	30	35	40	45	50
520	15	20	25	30	35	40	45	50	60
720	15	25	30	35	40	50	55	60	70
920	20	25	35	40	50	55	65	70	80
1120	20	30	40	45	55	65	70	80	90
1320	25	35	45	55	60	70	80	90	100
1520	30	40	50	60	70	80	90	100	110
1720	30	40	55	65	75	85	95	105	120
1920	35	45	60	70	80	95	105	115	130

- The height is a fixed size.
- Interim widths available in increments of 5 mm.

### Attenuation values

attenuation values								
63	125	250	500	1k	2k	4k	8k	Hz
11	10	11	13	16	23	25	28	dB

- The attenuation data is based on a comparable measurement between a recess of 520 x 520 mm and a louvre of the same size.
- In critical situations, please consult an acoustic adviser. For example in acoustically hard rooms and/or in case of a short distance between the source of noise, louvre and a specific place where the sound level needs to comply with certain standards.

### Note

- The listed dimensions are in mm.
- W x H is the recess size.
- It is recommended to fit a drainage option in the duct behind the louvres.
- The factory-fitted mounting frame is a 40 x 40 mm corner profile, which does not have standard mounting holes.

## Selection details

### BKVN

air volume		required free flow in m <sup>2</sup>																							
		0.015		0.02		0.025		0.03		0.04		0.05		0.06		0.08		0.1		0.125		0.15			
m <sup>3</sup> /s	m <sup>3</sup> /h	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)		
0.040	144	15	13	8	6	5	-																		
0.050	180	23	19	13	12	8	7	6	-																
0.060	216	33	23	19	17	12	12	8	8	5	-														
0.080	288	59	31	33	25	21	20	15	16	8	9	5	5												
0.100	360	91	37	51	30	33	25	23	22	13	15	8	10	6	6										
0.150	540					74	36	51	32	29	26	19	21	13	17	7	11	5	6						
0.200	720							91	40	51	33	33	28	23	25	13	18	8	13	5	9	4	5		
0.250	900									91	40	51	33	36	30	20	24	13	19	8	14	6	10		
0.300	1080									116	44	74	39	51	35	29	29	19	24	12	19	8	15		
0.400	1440											132	47	91	43	51	36	33	32	21	27	15	23		
0.500	1800															80	42	51	37	33	32	23	29		
0.600	2160															116	47	74	42	47	37	33	33		
0.800	2800																		84	45	59	41			
1.000	3600																		132	51	91	47			

air volume		required free flow in m <sup>2</sup>																							
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2			
m <sup>3</sup> /s	m <sup>3</sup> /h	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)	Δp <sub>t</sub> Pa	L <sub>WA</sub> dB(A)		
0.250	900	3	4																						
0.300	1080	5	9	3	4																				
0.400	1440	8	16	5	12	4	8																		
0.500	1800	13	22	8	17	6	13	3	7																
0.600	2160	19	27	12	22	8	18	5	12	3	7														
0.800	2800	33	35	21	30	15	26	8	19	5	15	4	11												
1.000	3600	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5								
1.500	5400	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7				
2.000	7200			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8		
2.500	9000					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14		
3.000	10800							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19		
4.000	14400									132	57	91	53	51	46	33	42	21	37	15	33	8	26		
5.000	18000											143	58	80	52	51	47	33	42	23	39	13	32		
6.000	21600													116	57	74	52	47	47	33	43	19	37		
8.000	28800															132	60	84	55	59	51	33	45		
10.000	36000																	132	61	91	57	51	50		

### General

- $L_{pA} = L_{WA} - 10$  dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

### Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:  
 $\Delta p_t = \text{table value} \times 1.2$   
 $L_{pA} = \text{table value} + 5$  dB.

## Free flow

H	B								
	320	520	720	920	1120	1320	1520	1720	1920
	m <sup>2</sup>								
<b>320</b>	0.0156	0.0276	0.0396	0.0516	0.0636	0.0756	0.0876	0.0996	0.1116
<b>520</b>	0.0312	0.0552	0.0792	0.1032	0.1272	0.1512	0.1752	0.1992	0.2232
<b>720</b>	0.0468	0.0828	0.1188	0.1548	0.1908	0.2268	0.2628	0.2988	0.3348
<b>920</b>	0.0624	0.1104	0.1584	0.2064	0.2544	0.3024	0.3504	0.3984	0.4464
<b>1120</b>	0.0780	0.1380	0.1980	0.2580	0.3180	0.3780	0.4380	0.4980	0.5580
<b>1320</b>	0.0936	0.1656	0.2376	0.3096	0.3816	0.4536	0.5256	0.5976	0.6696
<b>1520</b>	0.1092	0.1932	0.2772	0.3612	0.4452	0.5292	0.6132	0.6972	0.7812
<b>1720</b>	0.1248	0.2208	0.3168	0.4128	0.5088	0.6048	0.7008	0.7968	0.8928
<b>1920</b>	0.1404	0.2484	0.3564	0.4644	0.5724	0.6804	0.7884	0.8964	1.0044



## BMDRSO

### Weather louvre Aluminium

#### Available types

#### **B M D R S O**

- B** weather louvre
- M** wall louvre
- D** extruded aluminium
- R** round
- S** mesh
- O** not applicable

#### SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

#### Use

The round BMDRSO weather louvre is suitable for air supply or discharge.

#### Characteristics


Free flow: approx. 72 %

#### Version

##### Weather louvre

Frame:	aluminium
Vanes:	aluminium
Post-treatment:	none
Mesh:	10 x 10 mm, galvanised

## Dimensions



### Available dimensions, sizes and weights

model	d	D	A	C	kg
80	79	97	5	11	0.085
100	99	124	2	17	0.115
125	124	150	2	17	0.145
150	149	173	3	15	0.210
160	159	181	3	15	0.245
200	199	222	3.5	16.5	0.395
250	249	275	4	16	0.708
315	314	348	6.5	14.5	1.325
400	399	444	5	34	2.700
500	499	544	5	34	4.330

### Note

- The listed dimensions are in mm.
- Also suitable for indoor use.

### Fitting

- Depending on the use, sealant can be used.
- If mechanical strength is required, mount with a round duct in the recess.

## Selection details

### BMDRSO

air volume		model									
		80	100	125	150	160	200	250	315	400	500
m <sup>3</sup> /s	m <sup>3</sup> /h	Δpt Pa									
0.010	36	31	9								
0.015	54	69	22	7							
0.020	72		40	12	7						
0.030	108		90	29	16	11					
0.040	144			52	29	20	7				
0.060	216				65	48	18	6			
0.080	288					90	30	11			
0.100	360						47	18	8		
0.150	540							45	16	6	
0.200	720							80	30	12	5
0.300	1080								80	31	13
0.400	1440									46	19

### General

- It is permitted to interpolate the interim values.
- Pressure-loss data apply to drawing in air.

### Correction data

- When air is discharged, the values in the table need to be corrected with the following factors:  
 $\Delta pt = \text{table value} \times 0.83$