

BMUF-K

Weather louvre Burglar-proof version Blind fitting from the outside

Available types

B M U F - K

- B** weather louvre
 - M** wall louvre
 - U** set hot-dip galvanised steel vane 70 mm, with reinforcement strips
 - F** frame 54 mm
- **Mesh**
- Q** mesh, cold rolled (standard)
 - S** stainless steel insect mesh
- K** burglar-proof blind mounting with a mounting frame with spring clips for click mounting the louvre

SA-Select

Check SA-Select to create extended order codes and selection details online. **NB!** At this moment, SA-Select is only available in Dutch. But it is possible to create extended order codes and selection details online.

Use

The BMUFQK louvre is suitable for air supply or discharge. The louvre is mounted in the wall with a corresponding mounting frame with springs for click mounting the louvre. The louvre can be fitted from the outside of the building without disassembling the connection ducts. The louvre has been developed to replace existing, non burglar-proof, weather louvres.

Characteristics

Free flow: 20 - 55 % (depending on the height)
Weight: approx. 35 kg/m²

Version

Weather louvre


Frame: hot-dip galvanised steel
Vaness: hot-dip galvanised steel
Mesh: 10 x 10 mm, hot-dip galvanised steel
Mounting frame: hot-dip galvanised steel
Spring clips: stainless steel, centre-to-centre 300 mm

Optional

Insect mesh*: stainless steel, 2 x 2 mm

*The use of insect mesh reduces the net free flow and this has consequences for the design details. They are available in SA-Select.

Dimensions



Standard dimensions

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
325	■	■	■	■	■	■	■	■	■
525	■	■	■	■	■	■	■	■	■
825	■	■	■	■	■	■	■	■	■
1025	■	■	■	■	■	■	■	■	■
1225	■	■	■	■	■	■	■	■	■
1425	■	■	■	■	■	■	■	■	■
1625	■	■	■	■	■	■	■	■	■
1825	■	■	■	■	■	■	■	■	■
2025	■	■	■	■	■	■	■	■	■

Available dimensions

- Interim widths and heights available in increments of 5 mm.

Opmerking

- The louvre is fully hot-dip galvanized with a minimum zinc layer thickness according to NEN EN ISO 1461 (not centrifuged, average thickness 55 μm , 395 g/m^2).
- It is recommended to fit a drainage option in the duct behind the louvres.
- The listed dimensions are in mm.
- Recess size: $W + 30 \times H + 30$.

Selection details

BMUFQ

air volume		required free flow in m ²											
		0.05		0.06		0.08		0.1		0.125		0.15	
m ³ /s	m ³ /h	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)
0.080	288	5	5										
0.100	360	8	10	6	6								
0.150	540	19	21	13	17	7	11	5	6				
0.200	720	33	28	23	25	13	18	8	13	5	9	4	5
0.250	900	51	34	36	30	20	24	13	19	8	14	6	10
0.300	1080	74	39	51	35	29	29	19	24	12	19	8	15
0.400	1440	132	47	91	43	51	36	33	32	21	27	15	23
0.500	1800					80	42	51	37	33	32	23	29
0.600	2160					116	47	74	42	47	37	33	33
0.800	2800									84	45	59	41
1.000	3600									132	51	91	47

air volume		required free flow in m ²																						
		0.2		0.25		0.3		0.4		0.5		0.6		0.8		1.0		1.25		1.5		2		
m ³ /s	m ³ /h	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	Δp_t Pa	L_{pA} dB(A)	
0.250	900	3	4																					
0.300	1080	5	9	3	4																			
0.400	1440	8	16	5	12	4	8																	
0.500	1800	13	22	8	17	6	13	3	7															
0.600	2160	19	27	12	22	8	18	5	12	3	7													
0.800	2800	33	35	21	30	15	26	8	19	5	15	4	11											
1.000	3600	51	40	33	35	23	32	13	25	8	20	6	16	3	10	2	5							
1.500	5400	116	51	74	46	51	42	29	36	19	31	13	27	7	21	5	16	3	11	2	7			
2.000	7200			132	54	91	50	51	43	33	38	23	35	13	28	8	23	5	19	4	15	2	8	
2.500	9000					143	55	80	49	51	44	36	40	20	34	13	29	8	24	6	20	3	14	
3.000	10800							116	54	74	49	51	45	29	39	19	34	12	29	8	25	5	19	
4.000	14400									132	57	91	53	51	46	33	42	21	37	15	33	8	26	
5.000	18000											143	58	80	52	51	47	33	42	23	39	13	32	
6.000	21600													116	57	74	52	47	47	33	43	19	37	
8.000	28800														132	60	84	55	59	51	33	45		
10.000	36000																132	61	91	57	51	50		

Preferred range (approx. 4 m/s over net surface).

General

- $L_{pA} = L_{WA} - 10$ dB.
- It is permitted to interpolate the interim values.
- Sound and pressure loss data apply when the discharge goes to the outside.

Correction data

- When air is drawn in, the values in the table need to be corrected with the following factors:
 $\Delta p_t = \text{table value} \times 1,2$
 $L_{pA} = \text{table value} + 5$ dB.

Free flow

H	W								
	425	625	825	1025	1225	1425	1625	1825	2025
	m ²								
325	0.0488	0.0738	0.0988	0.1238	0.1488	0.1738	0.1988	0.2238	0.2488
525	0.0878	0.1328	0.1778	0.2228	0.2678	0.3128	0.3578	0.4028	0.4478
825	0.1463	0.2213	0.2963	0.3713	0.4463	0.5213	0.5963	0.6713	0.7463
1025	0.1853	0.2803	0.3753	0.4703	0.5653	0.6603	0.7553	0.8503	0.9453
1225	0.2243	0.3393	0.4543	0.5693	0.6843	0.7993	0.9143	1.0293	1.1443
1425	0.2633	0.3983	0.5333	0.6683	0.8033	0.9383	1.0733	1.2083	1.3433
1625	0.3023	0.4573	0.6123	0.7673	0.9223	1.0773	1.2323	1.3873	1.5423
1825	0.3413	0.5163	0.6913	0.8663	1.0413	1.2163	1.3913	1.5663	1.7413
2025	0.3803	0.5753	0.7703	0.9653	1.1603	1.3553	1.5503	1.7453	1.9403