



Room sensors,-control units, -controls

Individual room control
CO₂/RV/temperature/ventilation

Use

Solid Air supplies a complete range of room sensors, control units and controllers suitable for CO₂ and/or temperature control. In addition to the units with integrated CO₂ sensor, the Belimo room controllers (thermostats) type CR24 are also available for individual use. Differential room control based on temperature. For more general information on the possibilities of the In various products, we refer you to the document Solid Air room sensors, control units and controllers.

Characteristics

- Air-quality sensors and thermostats with several functionalities.
- Direct control of the VAV system.
- Stand-alone controls or can be incorporated into building-management systems.




Fitting

In accordance with supplied instructions.

Note

- Please consult our technical experts about extra possibilities and options.

Belimo room sensors/control units for CO₂/temperature control via GBS *1

version	product code	colors LED green yellow red	tempera- ture + Rel. moisture/ dew point + CO ₂	number of analog outputs + Standard outputs	MOD bus and BACNet	MP- BUS	NFC	commis- sioning with Belimo Assistant App via NFC	setpoint statement desired value for GBS. *2	power supply
 white cover against unwanted adjustments	22RTM-19-1	Yes	Yes	3, linear 0-10V	No	Yes	Yes	Yes	Temperature	24V AC/DC
 white cover with virtual display via Belimo Display App	P-22RTM-1900A-1				No					
	P-22RTM-1U00A-2				Yes					
 white cover with E-Paper like Display touch screen	P-22RTM-1900D-1				No					
	P-22RTM-1U00D-2	Yes	Temperature and ventilatie							




*1: Belimo sensors are intended to take temperature, relative humidity and CO₂ measurements and feed them back to the control panel control system. The control of field devices such as VAV units or reheaters must be achieved by a control system. With the above Belimo units, the lower and upper limit can be specified for the 0-10V feedback of the CO₂ signal. As a result, this Belimo Sensor can be used as a stand-alone CO₂ sensor for control of an LMV-D3-IMP (VAV unit).

*2 **Please note:** this is not a controller but only a setpoint for feedback to GBS for the desired value.

Belimo room sensors/controllers for 'stand alone' temperature control

thermostats	function/version	analogue output
CR24-B1	cooling only	0(2) -10V
CR24-B2	cooling and heating	cooling: 0(2)-10V heating: 3 point
CR24-B3	cooling and heating	cooling: 0(2)-10V heating: 3 point or 0-10V

Atal room sensors/controllers for 'stand alone' CO₂/temperature control

version	colors LED green yellow red	tempera- ture	rel. moisture /Dew- point	CO ₂	number of analog outputs + Standard output	analog output temperature	analoge output \ CO ₂	direct PID- control of VAV air valve with one analog output based on CO ₂ and temperature setpoint.	MOD bus and BACNet	power supply
 AT-VLC-ND-A2-RS white cover without display	Yes, switch- able	Yes	No	Yes, 0-2000 ppm	2, linear 0-10V	PID with setpoint for stand-alone control of heat exchanger (see figure 1) or linear for feedback to GBS.	PID with setpoint for stand-alone control (see figure 1) or linear for feedback GBS	No	Modbus RTU RS485	24V AC/DC
 AT-A2-RS-VAV white cover with display and control buttons				Yes, 0-5000 ppm						
 AT-VLX-A2-RS-VAV white cover with green, orange, red colored display based on CO ₂ and control buttons	No LED, but photo- chromatic display									